



PRODUCT OVERVIEW

The 2000 Series is a versatile terrace door that performs well in a variety of environments, from low rise garden apartments to high-rise multi-family residential buildings. Narrow sightlines create a sleek look that enhances the view.

STANDARD FEATURES

- › 1" Insulated tempered glass unit
- › XO / OX Configurations
- › Double thermal break interlock
- › Double perimeter weather-strip
- › Slim sight line
- › Full adjustable, self-lubricated ball-bearing tandem rollers
- › Rigid telescoping design
- › Matching fixed window (2050)
- › Heavy duty handles
- › Fiberglass mesh screen

OPTIONAL FEATURES

- › Stainless steel track cover (standard with HC rated and higher)
- › OXO / OOX / XOO Configurations
- › Flanges (1 1/2", 2")

AVAILABLE ACCESSORIES

- › Receptor System
- › Trim

MODEL	AAMA RATING	STRUCTURAL LOAD (psf)	TEST SIZE	WIND SPEED (mph)	AIR (cfm/ft ²)	WATER (psf)	U-VALUE ¹
2000	C-30	45	95" x 83"	25 (1.6 psf)	<0.2	4.5	0.36 - 0.45
2000	C-40	60	95" x 83"	25 (1.6 psf)	<0.2	7.5	0.36 - 0.45
2001-CW	CW-65	97.5	95" x 83"	50 (6.24 psf)	<0.2	10	0.36 - 0.45
2001-HC	HC-50	75	123" x 95"	50 (6.24 psf)	<0.2	10	0.36 - 0.45
2001-AW	AW-40	60	123" x 95"	50 (6.24 psf)	<0.2	10	0.36 - 0.45
2050 (FIXED)	AW-110	165	60" x 99"	50 (6.24 psf)	<0.1	12	0.38

Performance data based on testing by AAMA Accredited Laboratory, NFRC Simulation software or independent testing. Actual results will vary based on field conditions, locations, size/configurations or glazing options. Be sure to verify the performance requirements for your particular project. ¹ U-Values will vary depending on the glazing selected. Please contact Northern for further information.

