NORTHERN ARCHITECTURAL SYSTEMS

UW-5275 SSG

5” SILICONE STRUCTURAL GLAZED ULTRAWALL



PRODUCT OVERVIEW

Adaptable. Modular. Engineered.
Introducing the UltraWall 5275 SSG. Achieve a full SSG appearance with an integrated slab cover accommodating vision, spandrel or panel infills. Full receptor design allows for rapid interior installation.

STANDARD FEATURES

- Designed for 5ft x 9ft spans without the need for reinforcement
- Integrated slab cover
- 1” heat strengthened insulated glass
- Receptor design
- 4-sided Silicone Structurally Glazed

OPTIONAL FEATURES

- Shadowbox, UHPC, Panel or Spandrel infills
- Operable Vent and Door plug-in options
- Reinforcement for larger spans
- Glazing up to 1 5/16” to meet higher OITC values
- Glazing options to meet 2020 EEC C401 U-Value and SHGC requirements for fixed curtain wall

AVAILABLE ACCESSORIES

- Slab edge insulation
- Intermittent stabilization anchors
- Window washer bolts
- Parapet covers
- Deco caps or fins
- Trickle vents

CONTACT NORTHERN FOR PRECONSTRUCTION SUPPORT TO MEET THE NEEDS OF YOUR NEXT PROJECT

TYPE	AAMA RATING	STRUCTURAL LOAD (psf)	TEST SIZE	WIND SPEED (mph)	AIR (cfm/ft^2)	WATER (psf)	U-VALUE [1]
Fixed	AW-100	150	60” x 99”	50 (6.24 psf)	<0.1	15	0.38

Performance data based on testing by AAMA Accredited Laboratory, NFRC Simulation software or independent testing. Actual results will vary based on field conditions, locations, size/configurations or glazing options. Be sure to verify the performance requirements for your particular project. [1] U-Values will vary depending on the glazing selected. Please contact Northern for further information.

Proud Member

111 Central Avenue, Teterboro, NJ 07608 ♦ (201) 943 6400 ♦ info@nas-usa.com ♦ www.NorthernArchitecturalSystems.com