



PRODUCT OVERVIEW

The 9000 Series is optimized for contemporary projects with large openings, such as commercial office spaces, hotels and residential buildings. Heavy duty hardware enables the 9000 Series to achieve maximum durability.

STANDARD FEATURES

- > 1" Insulated glass unit
- > Custodial hex key tilt-disabling
- > Top sash anti-drift latch
- > Slim sightlines
- > Integral pull handles at top and bottom sash
- > Mating fixed window
- > Fiberglass mesh screen

OPTIONAL FEATURES

- > White-bronze Pole ring hardware
- > Muntin grids, applied and between the glass
- > Full top and bottom sash latch
- > Flange (2")

AVAILABLE ACCESSORIES

- > Receptor system
- > Panning
- > Trim

TYPE	AAMA RATING	STRUCTURAL LOAD (psf)	TEST SIZE	WIND SPEED (mph)	AIR (cfm/ft ²)	WATER (psf)	U-VALUE ¹
DH-Tilt	AW-45 / HC-65*	67.5 / 97.5	60" x 99"	50 (6.24psf)	<0.3	10	0.39 - 0.45
Fixed	AW-100 / 150	150 / 225	60" x 99"	50 (6.24psf)	<0.1	20	0.38

* Down-sized testing

Performance data based on testing by AAMA Accredited Laboratory, NFRC Simulation software or independent testing. Actual results will vary based on field conditions, locations, size/configurations or glazing options. Be sure to verify the performance requirements for your particular project. ¹ U-Values will vary depending on the glazing selected. Please contact Northern for further information.

