NORTHERN
ARCHITECTURAL SYSTEMS

2500 SERIES

3¼" FRAME DEPTH
TILT-IN DOUBLE HUNG

PRODUCT OVERVIEW

For those looking for an affordable and practical tilt double hung window, the 2500 Series is an excellent choice and particularly well suited for low-to-mid-rise projects.

STANDARD FEATURES

- ⅞" Insulated glass unit
- Burglar resistant anti-drift latch at top sash
- Tilt in sash for cleaning
- Slim sight line
- Integral extruded pull up & pull down handles
- Spiral balances calibrated for sash weight
- Mates with the 3050 Series fixed
- Male / Female Impost for composite units
- Fiberglass mesh screen

OPTIONAL FEATURES

- Metal tilt latches
- Class 5 Balances
- Snap latch at bottom rail
- Flange (1 ½", 2")
- Head expander

AVAILABLE ACCESSORIES

- Receptor system
- Panning
- Trim

MODEL	AAMA RATING	STRUCTURAL LOAD (psf)	TEST SIZE	WIND SPEED	AIR (cfm/ft^2)	WATER (psf)	U-VALUE [1]
2501	C-50 / 60	75 / 90	56 x 91"	25 (1.6 psf)	<0.2	7.5 / 9	0.36 - 0.45

Performance data based on testing by AAMA Accredited Laboratory, NFRC Simulation software or independent testing. Actual results will vary based on field conditions, locations, size/configurations or glazing options. Be sure to verify the performance requirements for your particular project. [1] U-Values will vary depending on the glazing selected. Please contact Northern for further information.

Proud Member

111 Central Avenue, Teterboro, NJ 07608 ♦ (201) 943 6400 ♦ info@nas-usa.com ♦ www.NorthernArchitecturalSystems.com