



PRODUCT OVERVIEW

The 3050 Series is a fixed window with slim sightlines that compliments the other 3 1/4" products in our portfolio. It is also suitable for smaller openings as an add-on to other windows.

STANDARD FEATURES

- › 1" Insulated glass
- › Slim Sight Line
- › Rigid "Butt-Type" Construction
- › Thermally broken frame

OPTIONAL FEATURES

- › Flanges (3/4", 1", 1 1/2", 2", 2 1/2")
- › Head expander

AVAILABLE ACCESSORIES

- › Receptor system
- › Trim



TYPE	AAMA RATING	STRUCTURAL LOAD (psf)	TEST SIZE	WIND SPEED (mph)	AIR (cfm/ft ²)	WATER (psf)	U-VALUE ¹
Fixed	AW-80	120	60" x 99"	50 (6.24psf)	<0.1	12	0.38
Fixed	HC-85*	127.5	72" x 72"	50 (6.24psf)	<0.1	12	0.38

* Down-sized testing

Performance data based on testing by AAMA Accredited Laboratory, NFRC Simulation software or independent testing. Actual results will vary based on field conditions, locations, size/configurations or glazing options. Be sure to verify the performance requirements for your particular project. ¹ U-Values will vary depending on the glazing selected. Please contact Northern for further information.

