NORTHERN
ARCHITECTURAL SYSTEMS

7050 SERIES

2 ½" - 3 ¼" FRAME DEPTH
FIXED

PRODUCT OVERVIEW

The 7050 Series is built for durability and strength. It is designed for use as a standalone window in larger openings or as a transom with the 7000 Series and 7600 Series products.

STANDARD FEATURES

- 1" Insulated glass
- Slim sightlines
- Mates with the 7000 Series and 7960 Series Products

OPTIONAL FEATURES

- Up to 1 ⅜" insulated glass
- Muntin Grids, applied and between the glass
- Strutted design dual finish or 2-tone
- Applied Flange (1", 1 ½", 2½", 3 ¼")

AVAILABLE ACCESSORIES

- Receptor System
- Panning
- Trims

TYPE	AAMA RATING	STRUCTURAL LOAD (psf)	TEST SIZE	WIND SPEED (mph)	AIR (cfm/ft^2)	WATER (psf)	U-VALUE [1]
Fixed	AW-100	150	60" x 99"	50 (6.24psf)	<0.1	12	0.38

Performance data based on testing by AAMA Accredited Laboratory, NFRC Simulation software or independent testing. Actual results will vary based on field conditions, locations, size/configurations or glazing options. Be sure to verify the performance requirements for your particular project. [1] U-Values will vary depending on the glazing selected. Please contact Northern for further information.

Proud Member

111 Central Avenue, Teterboro, NJ 07608 ♦ (201) 943 6400 ♦ info@nas-usa.com ♦ www.NorthernArchitecturalSystems.com