



## PRODUCT OVERVIEW

Durable and featuring a high performance structural design the PW-252 is the perfect solution to low to mid rise, multi span applications. Stick fabricated with varying mullion depths this pressure wall is versatile and proven to meet monumental and aesthetically pleasing wall requirements.

## STANDARD FEATURES

- › Outside glazed captured Curtain Wall
- › 2-1/2" sight line
- › 6-1/2" or 7-1/2" depth systems
- › Concealed Fastener Joinery creates smooth, monolithic appearance
- › Shear Block fabrication method
- › Bronze or Clear Anodized finish

## OPTIONAL FEATURES

- › Corners and Splayed Mullions
- › Integrated entrance framing systems
- › Silicone-compatible glazing materials, including structural glazing
- › Dual Finish or paint
- › Steel reinforcement
- › Sun Screens
- › Backpans
- › Deep profile and bull nose covers
- › Deep and heavy-weight mullions

## AVAILABLE ACCESSORIES

- › Standard F and T anchors

STRUCTURAL LOAD (psf)	TEST SIZE	WIND SPEED (mph)	STATIC AIR (cfm/ft <sup>2</sup> )	DYNAMIC AIR (cfm/ft <sup>2</sup> )	STATIC WATER (psf)	DYNAMIC WATER (psf)
67.5	155.5" x 256.75"	50 (6.24psf)	0.01	0.01	15	15

Performance data based on testing by AAMA Accredited Laboratory, NFRC Simulation software or independent testing. Actual results will vary based on field conditions, locations, size/configurations or glazing options. Be sure to verify the performance requirements for your particular project. <sup>1</sup> U-Values will vary depending on the glazing selected. Please contact Northern for further information.

